

**REMARKS**

Entry of this amendment prior to examination of the above-identified application is respectfully requested.

**AUTHORIZATION**

The Commissioner is hereby authorized to charge any additional fees, which may be required for this Preliminary Amendment, or credit any overpayment, to Deposit Account No. 19-3140.

Respectfully submitted,

Jean C. Edwards  
Jean C. Edwards  
Registration No. 41,728

Sonnenschein Nath & Rosenthal  
1301 K St., N.W.  
East Tower, Suite 600  
Washington, D.C. 20005  
Telephone: 202/408-6428  
Facsimile: 202/408-6399  
**December 11, 2001**

25042680\V-1

10005319 121101

**APPENDIX**

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

**IN THE CLAIMS:**

70. The acoustic conversion device according to claim [71] 69, wherein the thickness of at least one portion in the longitudinal direction of the curved portion is made thicker, or a high elastic modulus portion is provided by increasing the density of an elastic body forming the one portion in the longitudinal direction of the curved portion.

**IN THE ABSTRACT OF THE DISCLOSURE:**

A flat acoustic conversion device includes two magnets disposed so that their magnetic poles face upward and are adjacent to or in contact with one another, and the magnetic pole faces of different polarities are disposed alternately; a vibrating member disposed on the top surface of the yoke; coil pairs wound in helical form and disposed at front and reverse surfaces of the vibrating membrane; such that magnetic flux traveling in a direction substantially parallel to a surface of the vibrating membrane becomes a maximum, and interlinks with the coil pairs. When current is supplied to the coils, a direction of force which the current receives from a magnetic field is substantially orthogonal to the surface of the vibrating membrane, and force in a direction along the surface of the vibrating membrane becomes extremely low. Thus, noise components can be reduced such that sound quality can be improved.

[Flat, quadrangular permanent magnets m18, m28, m38 are disposed on a yoke 20 with their magnetic pole faces facing upward and so as to be adjacent to one another or contact one another, and such that magnetic pole faces of different polarities are disposed alternately. A vibrating membrane 26 is

5